

TM500A75 SERIES (20.0" diameter)



SPECIFICATIONS

50 HP

V (ft/min) M/G	750 4/S2	590 4/S2	468 4/S2	368 4/S2
Belt Pull (lbs)	2199	2795	3524	4481
Drum RPM	143	113	89	70

40 HP

V (ft/min) M/G	750 4/S2	590 4/S2	468 4/S2	368 4/S2
Belt Pull (lbs)	1763	2241	2825	3592
Drum RPM	143	113	89	70

30 HP

V (ft/min) M/G	750 4/S2	590 4/S2	468 4/S2	368 4/S2
Belt Pull (lbs)	1322	1680	2119	2694
Drum RPM	143	113	89	70

25 HP

V (ft/min) M/G	750 4/S2	590 4/S2	468 4/S2	368 4/S2
Belt Pull (lbs)	1102	1400	1766	2245
Drum RPM	143	113	89	70

20 HP

V (ft/min) M/G	500 6/S2	393 6/S2	312 6/S2	245 6/S2
Belt Pull (lbs)	1322	1680	2119	2694
Drum RPM	95	75	60	47

15 HP

V (ft/min) M/G	375 8/S2	295 8/S2	234 8/S2	184 8/S2
Belt Pull (lbs)	1322	1680	2119	2694
Drum RPM	72	56	45	35

V = Belt Speed (ft/min)

M/G = Motor/Gear Reducer Configuration (at rated horsepower)

High Speed
Low Torque



Low Speed
High Torque