

TM915A160 Drum Motor

500.0 HP

V (ft/min) M/G	745 4/PL2	627 4/PL2	550 4/PL2
Belt Pull (lbf)	21483	25526	29100
Drum RPM	79	67	58

400.0 HP

V (ft/min) M/G	745 4/PL2	627 4/PL2	550 4/PL2
Belt Pull (lbf)	17187	20421	23280
Drum RPM	79	67	58

350.0 HP

V (ft/min) M/G	745 4/PL2	627 4/PL2	550 4/PL2
Belt Pull (lbf)	15024	17860	20370
Drum RPM	79	67	58

300.0 HP

V (ft/min) M/G	745 4/PL2	627 4/PL2	550 4/PL2
Belt Pull (lbf)	12890	15316	17460
Drum RPM	79	67	58

250.0 HP

V (ft/min) M/G	745 4/PL2	627 4/PL2	550 4/PL2
Belt Pull (lbf)	10742	12763	14550
Drum RPM	79	67	58


250.0 HP

V (ft/min) M/G	496 6/PL2	417 6/PL2	365 6/PL2
Belt Pull (lbf)	16202	19259	21966
Drum RPM	53	44	39

V = Belt Speed (ft/min)

M/G = Motor/Gear Reducer Configuration (at rated horsepower)

High Speed
Low Torque



Low Speed
High Torque